

Safety Data Sheet
Non-Smoke

PRODUCT NAME: Non-Smoke - Dakota 15 spraytech

PRODUCT CODE: 1171740

PRODUCT USE: Air Freshener

COMPANY NAME: Dakota Products, Inc.

COMPANY ADDRESS: P.O. Box 1897, Sioux Falls, SD 57108

COMPANY PHONE: 605-368-2166

EMERGENCY PHONE: 800-255-3924

SECTION I - IDENTIFICATION

SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Liquefied Gas

Skin Irritant: Category 2

Eye Irritant: Category 2A

Aspiration Hazard: Category 1A

Sensitization - Skin: Category 1A

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

This product contains the following percentage of chemicals of unknown toxicity: 3%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves and eye protection. Avoid breathing fumes/spray. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	40-70%
Isoparaffinic Hydrocarbon	64742-47-8	10-30%
Propane/n-Butane	68476-86-8	10-30%
Fragrance	mixture	3-7%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting.

INHALATION: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

SKIN: Immediately wash with soap and water for 15 minutes. Seek medical attention if irritation persists.

ACUTE HEALTH HAZARDS: Acute, Inhalation of vapors may be narcotic or anesthetic. Ingestion of liquid will cause gastrointestinal distress, irritation, and possibly nausea. Liquid or vapors may be irritating to skin and eyes.

CHRONIC HEALTH HAZARDS: May cause damage to the following organs: kidneys, liver, skin, CNS depression.

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

Safety Data Sheet
Non-Smoke

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, and alcohol foam.
UNSATURABLE EXTINGUISHING MEDIA: Water spray/stream.
SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers. Shut off all sources of ignition.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.
SPILL: Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, state and federal regulations.
WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.
RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.
OTHER PRECAUTIONS: Keep out of the reach of children. Follow label instructions exactly. Avoid breathing fumes/vapors.
INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, some plastics.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
Isoparaffinic Hydrocarbon	400 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Fragrance	Not Established	Not Established

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.
RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved organic vapor respiratory protection if listed exposure limits (section VIII) are exceeded.
PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves
ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Off white spray mist
ODOR: Characteristic Odor
ODOR THRESHOLD: N/D
BOILING POINT: >130°F
FREEZING POINT: N/D
FLAMMABILITY: Extremely Flammable Aerosol
FLASH POINT: N/D
AUTOIGNITION TEMPERATURE: N/D
LOWER FLAMMABILITY LIMIT: N/A
UPPER FLAMMABILITY LIMIT: N/A
VAPOR PRESSURE (mm Hg): > 180 @ 70°F (21°C)
VAPOR DENSITY (AIR=1): > 2 @ 70°F (21°C)

EVAPORATION RATE: > 3 (Fast)
SPECIFIC GRAVITY (H2O=1): 0.790
pH: N/A
SOLIDS (%): N/D
SOLUBILITY IN WATER: 0%
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
VOLATILITY INCLUDING WATER (%): 100%
VOLATILE ORGANIC COMPOUNDS (VOC): 27%
DIELECTRIC STRENGTH (Volts): N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X - STABILITY AND REACTIVITY DATA

REACTIVITY: None Known
CHEMICAL STABILITY: Stable
CONDITIONS TO AVOID: Excess heat, open flame, sparks, electric equipment, ignition sources, and incompatible materials.
INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, some plastics.
HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon
POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI - TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Acetone - 67-64-1 - Oral LD50: Acute: 5800 mg/kg [Rat]. 3000 mg/kg [Mouse]. 5340 mg/kg [Rabbit]. Skin LD50: 20000.0 mg/kg (Rabbits) Inhalation (LC50): 50100 mg/m 8 hours [Rat]. 44000 mg/m 4 hours [Mouse]. 21000 ppm (Cats).
Isoparaffinic Hydrocarbon - 64742-47-8 - Oral LD50: Acute: > 15000 mg/kg (Rat), Skin LD50: > 5g/kg (Rat): Inhalation LC50 > 5mg/L (4-hr., Rat).

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: Causes irritation, may cause conjunctivitis with possible corneal injury.
INGESTION: May cause gastrointestinal irritation, nausea, diarrhea, vomiting, aspiration hazard.
INHALATION: May cause irritation to the respiratory tract, dizziness, headaches, nausea, unconsciousness, central nervous system depression.
SKIN: Causes localized defatting, irritation, may be absorbed through skin with systemic effects.
MEDICAL CONDITION AGGRAVATED: Pre-existing conditions of the skin, liver, CNS, and kidneys
ACUTE HEALTH HAZARDS: Acute, Inhalation of vapors may be narcotic or anesthetic. Ingestion of liquid will cause gastrointestinal distress, irritation, and possibly nausea. Liquid or vapors may be irritating to skin and eyes.
CHRONIC HEALTH HAZARDS: May cause damage to the following organs: kidneys, liver, skin, CNS depression.
CARCINOGENICITY: OSHA: Not Classified ACGIH: A5 - Not suspected NTP: N/A IARC: N/A OTHER: N/A

SECTION XII - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Acetone - 67-64-1 - Ecotoxicity in water (LC50): 5540 mg/l 96 hours [Trout]. 8300 mg/l 96 hours [Bluegill]. 7500 mg/l 96 hours [Fathead Minnow]. 0.1 ppm any hours [Water flea]. Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.
BIODEGRADABILITY: Component or components of this product are not biodegradable.
BIOACCUMULATION: Components in this mixture can bioaccumulate in aquatic organisms.
SOIL MOBILITY: This product is mobile in soil.
OTHER ECOLOGICAL HAZARDS: None Known

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.
RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Safety Data Sheet
Non-Smoke

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKAGING GROUP: N/A

AIR SHIPMENT
PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950

SHIPPING BY WATER:
VESSEL (IMO/MDG)
PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.
= 5,000 lbs
CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity

SARA 311/312 HAZARD CATEGORIES: Fire Hazard

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, RTK - RI, PA, FL, MN, MA, NJ, Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339); Acetone TSCA 8(b) inventory;
Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone

INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH: 1
NFPA FLAMMABILITY: 3
NFPA REACTIVITY: 0
NFPA OTHER: None
HMIS HEALTH: 1
HMIS FLAMMABILITY: 3
HMIS REACTIVITY: 0
HMIS PROTECTION: B

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Jonathon Jarvis
DATE PREPARED: 11/18/2013
REVISION DATE: 06/08/2015

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or implied, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.