

acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

Glacier Glaze Trade name

OPA Ref# PPGG00QT, PPGG00GL

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses vehicle polish

1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC 10963 Leroy Drive Northglenn

CO 80233 United States

Telephone: 1.800.875.6320, 1.303.289.6320 Telefax e-mail: info@bbblending.com

Website: bbblending.com

Competent person responsible for the SDS

Robert Blahnik

e-mail (competent person) bblahnik@bbblending.com

1.4 **Emergency telephone number**

> USA 1.800.535.5053, INTL 1.352.323.3500 Emergency information service

24 hour emergency telephone number.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Annex | Hazard class and category | - | Hazard s | tatement code(s) | |
|-------|---|---|----------|------------------|-------|
| A.2 | skin corrosion/irritation | | Cat. 2 | (Skin Irrit. 2) | H315 |
| A.7 | reproductive toxicity | | Cat. 2 | (Repr. 2) | H361f |
| A.10 | aspiration hazard | | Cat. 1 | (Asp. Tox. 1) | H304 |

Remarks

For full text of H-phrases: see SECTION 16.

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word danger



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

Pictograms

GHS07, GHS08



Hazard statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H361f Suspected of damaging fertility.

Precautionary statements

Precautionary statements - prevention

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Precautionary statements - response

IF SWALLOWED: immediately call a POISON CENTER or doctor/physician.

IF exposed or concerned: get medical advice/attention.

Do NOT induce vomiting.

Precautionary statements - disposal

Dispose of contents/container to industrial combustion plant.

Hazardous ingredients for labelling

dimethylsiloxane cyclic tetramer, Hydrocarbons, C13-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics, odorless mineral spirits

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Hazard | class and cat- egory | Hazard statement | Pictograms |
|----------------------------------|----------------------|-----------|----------------------------|---|------------------------------|------------|
| odorless mineral spirits | CAS No 64742-48-9 | 10 - < 25 | B.6 A.2 A.8D A.10 | Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1 | H226 H315 H336 H304 | |
| dimethylsiloxane cyclic tetramer | CAS No 556-67-2 | 10 - < 25 | B.6 A.7 | Flam. Liq. 3 Repr. 2 | H226 H361f | |
| decamethylcyclopentasiloxane | CAS No 541-02-6 | 1 - < 5 | B.6 | Flam. Liq. 4 | H227 | |



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO2)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

Incompatible substances or mixtures

Observe compatible storage of chemicals.

Control of the effects

Protect against external exposure, such as

frost

Consideration of other advice

Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

| Coun- try | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Source |
|--------------|---|------------|------------|--------------|----------------|---------------|-----------------|-------------|
| US | petroleum distillates (naphtha) (rubber solvent) | 64742-48-9 | PEL | 500 | 2,000 | | | 29 CFR OSHA |

Notation

TWA

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified.

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

Skin protection

· hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid (viscous)

Color off-white

Odor sweet

Other physical and chemical parameters

pH (value) not determined

Melting point/freezing point not determined

Initial boiling point and boiling range 100 °C

Flash point >100 °C at 101.3 kPa >212 °F at 1 atm (closed cup)

Evaporation rate not determined

Flammability (solid, gas) not relevant (fluid)

Explosive limits

• lower explosion limit (LEL) 0.7 vol%

• upper explosion limit (UEL) 5.4 vol%

Vapor pressure 132 Pa at 25 °C

Density $0.99 \, ^{\rm g}/_{\rm cm^3}$ at 25 $^{\circ}{\rm C}$

Solubility(ies) not determined



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

Partition coefficient

n-octanol/water (log KOW)

This information is not available.

Auto-ignition temperature 325 °C

Viscosity not determined

Explosive properties none
Oxidizing properties none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

Physical stresses which might result in a hazardous situation and have to be avoided strong shocks

10.5 Incompatible materials

There is no additional information.

Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

Skin corrosion/irritation

Causes skin irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Summary of evaluation of the CMR properties

Suspected of damaging fertility.

Shall not be classified as carcinogenic.

Shall not be classified as germ cell mutagenic.

Carcinogenicity

• National Toxicology Program (United States):

none of the ingredients are listed

• IARC Monographs

none of the ingredients are listed

Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity (acute)

Toxic to aquatic organisms.

Aquatic toxicity (acute) of components of the mixture

| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
|----------------------------------|----------|----------|-------------------------------------|-----------------------|---------------|
| dimethylsiloxane cyclic tetramer | 556-67-2 | LC50 | >22 ^{µg} / _l | fish | 96 hours |
| dimethylsiloxane cyclic tetramer | 556-67-2 | EC50 | >1,000 ^{mg} / ₁ | aquatic invertebrates | 96 hours |
| decamethylcyclopentasilox ane | 541-02-6 | LC50 | >16 ^{µg} / ₁ | fish | 96 hours |
| decamethylcyclopentasilox ane | 541-02-6 | EC50 | >2.9 ^{µg} / ₁ | aquatic invertebrates | 48 hours |

Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
|----------------------------------|------------|----------|------------------------------------|-----------------------|---------------|
| odorless mineral spirits | 64742-48-9 | EC50 | 15.41 ^{mg} / ₁ | microorganisms | 40 h |
| dimethylsiloxane cyclic tetramer | 556-67-2 | LC50 | 10 ^{µg} / ₁ | fish | 14 d |
| dimethylsiloxane cyclic tetramer | 556-67-2 | EC50 | >500 ^{mg} / ₁ | aquatic invertebrates | 24 h |



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
|-------------------------------|----------|----------|----------------------------------|-----------------------|---------------|
| decamethylcyclopentasilox ane | 541-02-6 | LC50 | >16 ^{µg} / _l | fish | 14 d |
| decamethylcyclopentasilox ane | 541-02-6 | EC50 | >15 ^{µg} / ₁ | aquatic invertebrates | 21 d |

12.2 Process of degradability

Data are not available.

Degradability of components of the mixture

| Name of substance | CAS No | Process | Degradation rate | Time |
|----------------------------------|----------|---------------------------|------------------|------|
| dimethylsiloxane cyclic tetramer | 556-67-2 | carbon dioxide generation | 3.7 % | 29 d |
| decamethylcyclopentasilox ane | 541-02-6 | carbon dioxide generation | 0.14 % | 28 d |

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

| Name of substance | CAS No | BCF | Log KOW | BOD5/COD |
|----------------------------------|----------|--------|---------|----------|
| dimethylsiloxane cyclic tetramer | 556-67-2 | 12,400 | 4.45 | |
| decamethylcyclopentasilox ane | 541-02-6 | 7,060 | 4.76 | |

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

13.3 Remarks

14.1

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

| 14.2 | UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LI- OUID, N.O.S. |
|------|-------------------------|--|

Hazardous constituents decamethylcyclopentasiloxane

14.3 Transport hazard class(es)

UN number

Class 9 (miscellaneous dangerous substances and articles) (environmentally

hazardous

3082

14.4 Packing group III (substance presenting low danger)

14.5 Environmental hazards hazardous to the aquatic environment

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

• Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

Class 9
Packing group III

Danger label(s) 9 + "fish and tree"



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31



Environmental hazards yes (hazardous to water)

Special provisions (SP) 8, 146, 173, 335, IB3, T4, TP1, TP29

ERG No 171

• International Maritime Dangerous Goods Code (IMDG)

UN number 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LI-

QUID, N.O.S.

Class 9

Subsidiary risk(s) -

Marine pollutant yes (hazardous to water)

Packing group III

Danger label(s) 9 + "fish and tree"

Special provisions (SP) 274, 335, 909

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L

EmS F-A, S-F

Stowage category A

• International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

Class 9

Environmental hazards yes (hazardous to water)

Packing group III

Danger label(s) 9 + "fish and tree"

Special provisions (SP) A97, A158

Excepted quantities (EQ) E1
Limited quantities (LQ) 30 kg



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Industry or sector specific available guidance(s)

• NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

| Category | Rating | Description |
|-------------------------------|--------|--|
| Chronic | * | Chronic (long-term) health effects may result from repeated overexposure. |
| Health | 2 | Temporary or minor injury may occur. |
| Flammability | 1 | Materials that must be preheated before ignition can occur. |
| Physical hazard | 0 | Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives. |
| Personal protective equipment | - | |

• NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States) - National Fire Protection Association (United States)

| Category | Degree of hazard | Description |
|----------------|---------------------|---|
| Flammability | 1 | Materials that must be preheated before ignition can occur. |
| Health | 0 | Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material. |
| Instability | 0 | Materials that are normally stable, even under fire conditions. |
| Special hazard | | |

Relevant European Union (EU) safety, health and environmental provisions

Classification according to GHS (1272/2008/EC, CLP)

Skin corrosion/irritationCat. 2(Skin Irrit. 2)Reproductive toxicityCat. 2(Repr. 2)Aspiration hazardCat. 1(Asp. Tox. 1)

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

SECTION 16: Other information

16.2 Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations | | | | |
|--------------------|--|--|--|--|--|
| 29 CFR OSHA | 29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits) | | | | |
| 49 CFR US DOT | 49 CFR § 40 U.S. Department of Transportation | | | | |
| ADR | cord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning e International Carriage of Dangerous Goods by Road) | | | | |
| Asp. Tox. | iration hazard | | | | |
| BCF | BioConcentration Factor | | | | |
| BOD | Biochemical Oxygen Demand | | | | |
| CAS | Chemical Abstracts Service | | | | |
| CLP | Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures | | | | |
| CMR | Carcinogenic, Mutagenic or toxic for Reproduction | | | | |
| COD | chemical oxygen demand | | | | |
| DMEL | Derived Minimal Effect Level | | | | |
| DNEL | Derived No-Effect Level | | | | |
| EmS | Emergency Schedule | | | | |
| ERG No | Emergency Response Guidebook - Number | | | | |
| Flam. Liq. | flammable liquid | | | | |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations | | | | |
| IARC Monographs | IARC Monographs on the Evaluation of Carcinogenic Risks to Humans | | | | |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) | | | | |
| ICAO | International Civil Aviation Organization | | | | |
| IMDG | International Maritime Dangerous Goods Code | | | | |
| log KOW | n-octanol/water | | | | |
| MARPOL | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant) | | | | |
| NFPA® 704 | National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States) | | | | |
| NPCA-HMIS® III | National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition | | | | |
| OSHA | Occupational Safety and Health Administration (United States) | | | | |
| PBT | Persistent, Bioaccumulative and Toxic | | | | |
| PNEC | Predicted No-Effect Concentration | | | | |
| ppm | parts per million | | | | |
| Repr. | reproductive toxicity | | | | |
| Skin Corr. | corrosive to skin | | | | |



acc. to OSHA, Appendix D to § 1910.1200

Glacier Glaze

Version number: GHS 1.0 Date of compilation: 2015-03-31

| Abbr. | Descriptions of used abbreviations |
|-------------|--|
| Skin Irrit. | irritant to skin |
| STOT SE | specific target organ toxicity - single exposure |
| vPvB | very Persistent and very Bioaccumulative |

16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200
- 49 CFR § 172.101 Hazardous Materials Table (DOT)

16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

16.5

List of relevant phrases (code and full text as stated in chapter 2 and 3)

| | • • • |
|-------|--|
| Code | Text |
| H226 | flammable liquid and vapor |
| H227 | combustible liquid |
| H304 | may be fatal if swallowed and enters airways |
| H315 | causes skin irritation |
| H336 | may cause drowsiness or dizziness |
| H361f | suspected of damaging fertility |

16.7 Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.